

PRODUCT SPECIFICATION SHEET

GENERAL NOTES TO SPECIFIER:

THIS PRODUCT SPECIFICATION SHEET IS INTENDED TO HELP DESIGN PROFESSIONALS AND ARCHITECTS TO SPECIFY SHINNOKI SHADOW EUCALYPTUS PREFINISHED PANELS IN SPECIFICATIONS FOR WALL AND/OR CEILING PANELLING; CASEWORK AND OTHER SIMILAR ARCHITECTURAL WOODWORK.

SHINNOKI PANELS ARE PREFINISHED REAL WOOD VENEER PANELS, BRUSHED, STAINED AND LACQUERED THAT DO NOT REQUIRE ANY OTHER FINISH.

SPECIFIED MATERIAL DETAILS:

1. Material name: Shinnoki Prefinished Wood Panel, Shadow Eucalyptus
2. Veneer species: Fumed Eucalyptus
3. Splicing method: Mixmatch splicing
4. Finish: Shadow Eucalyptus color protected with six layers of UV lacquer, applied by a roller and intermediately cured. Panel dimensions: $\frac{3}{4}$ " thick x 4' wide x 9' long / 2790mm long x 1240mm wide x 19mm thick.
5. Executions:
 - Exclusive: Both sides of the panel have Shinnoki quality veneer, for the most harmonious look available.
 - Premium: Shinnoki quality veneer on the front side. The back has the Shinnoki look and feel, while allowing for a bit more character in the veneer.
6. Manufacturer and local contact:

Decospan NV
Industriezone Grensland
Lageweg 33, 8930 Menen – Belgium
Tel: +32 56 52 88 00
info@decospan.com
7. Physical / mechanical properties:

• Gloss:	7± 3 (60°)
• Hardness of the lacquer	4 N
• Colour fastness	Grade >6
• Colour stability	Class 4/5
• Reflection	6
• Flame spread	D-S ₁ -d ₀
• FSC certified MDF core	Yes
• FSC certified final product	Yes
• PCP	PCP-free
• Formaldehyde Emission	E1 (non-added formaldehyde)
• Lamination	HPLT ¹ press procedure and DSI-method ²
8. Warranty: 2 years

¹ High pressure, low temperature

² double sided impregnation