SHINNOKI® PREFINISHED WOOD PANELS BURLEY OAK

PRODUCT SPECIFICATION SHEET

GENERAL NOTES TO SPECIFIER:

THIS PRODUCT SPECIFICATION SHEET IS INTENDED TO HELP DESIGN PROFESSIONALS AND ARCHITECTS TO SPECIFY SHINNOKI BURLEY OAK PREFINISHED PANELS IN SPECIFICATIONS FOR WALL AND/OR CEILING PANELLING; CASEWORK AND OTHER SIMILAR ARCHITECTURAL WOODWORK.

SHINNOKI PANELS ARE PREFINISHED REAL WOOD VENEER PANELS, BRUSHED, STAINED AND LACQUERED THAT DO NOT REQUIRE ANY OTHER FINISH.

SPECIFIED MATERIAL DETAILS:

- 1. Material name: Shinnoki Prefinished Wood Panel, Burley Oak
- 2. Veneer species: European White Oak
- 3. Splicing method: Mixmatch splicing
- 4. Finish: Burley Oak color protected with six layers of UV lacquer, applied by a roller and intermediately cured. Panel dimensions: ³/₄" thick x 4' wide x 9' long / 2790mm long x 1240mm wide x 19mm thick.
- 5. Executions:
 - Exclusive: Both sides of the panel have Shinnoki quality veneer, for the most harmonious look available.
 - Premium: Shinnoki quality veneer on the front side. The back has the Shinnoki look and feel, while allowing for a bit more character in the veneer.
- 6. Manufacturer and local contact:

Decospan NV Industriezone Grensland Lageweg 33, 8930 Menen – Belgium Tel: +32 56 52 88 00 info@decospan.com

- 7. Physical / mechanical properties:
 - Gloss:
 - Hardness of the lacquer
 - Colour fastness
 - Colour stability
 - Reflection
 - Flame spread
 - FSC certified MDF core
 - FSC certified final product
 - PCP
 - Formaldehyde Emission
 - Lamination

 $7 \pm 3 (60^{\circ})$ 4 NGrade >6 Class 4/5 7 D-S₁-d₀ Yes Yes PCP-free E1 (non-added formaldehyde) HPLT¹ press procedure and DSI-method²

8. Warranty: 2 years

¹ High pressure, low temperature ² double sided impregnation

DECOSPAN.

Industriezone Grensland Lageweg 33, 8930 Menen - Belgium Tel +32 56 52 88 00 info@decospan.com

